



a 2700 Wagner Place, Maryland Heights, MO 63043
t 314.785.6978
f 314.785.6942
w www.renaissancepolymers.com

PRODUCT DATA BULLETIN

Product **ADHESIVE 6266**

Application Lamination of High Density Polyethylene, Polypropylene, Mylar and Other Polymeric Films to Kraft

Physical Properties

Form	Liquid
Base	Emulsion Polymer
Color	White (film dries clear)
Odor	Slight Acetate
Solids	52+/-1%
pH	4.5 - 5.5
Viscosity	800 - 1200 cps
Pounds per Gallon	9.0
Inflammable	No
Usable After Freezing	Yes

Performance

Speed of Set	Fast
Water Resistance	Good
Flexibility	Good
Hygroscopic	No

Handling and Application

Storage Life	One Year
Store In	60-90°F
Dilution	As Required
Diluent	Water
Running Temperature	60-90°F
Film Application	As Required
Clean Up	Hot Water

REMARKS

Protect from freezing
The formulation of this product complies with F.D.A. Regulations concerning Food Packaging Adhesives/F.D.A. Status 21CFD175.105, 21CFD175.125 and 21CFD121.2520 "Adhesives."
Revision Date: 11-11-13

Because we cannot anticipate or control the many different conditions under which our products may be used, we do not guarantee the applicability of the accuracy of this information or the suitability of our products in any given situation. Users of our products should make their own tests to determine the suitability of each such product for their particular purposes. The products discussed are sold without warranty, either expressed or implied, and buyer assumes all responsibility for loss or damage arising from the handling and use of our products, whether done in accordance with directions or not. Also, statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.